

Professional Breath Alcohol Tester

For over 25 years, Lifeloc Technologies has provided advanced alcohol testing equipment & training for Law Enforcement and Corrections Professionals. We are the leader in product innovation, precision instruments, ease of use and Five Star customer care.

Lifeloc FC Series

Professional Breath Alcohol Tester

Unlock the Power of Alcohol Testing

Lifeloc FC Series

Platinum Fuel Cell with lifetime warranty	Unit Comparison	FC5	FC10	FC10 ^{Plus}	FC20	FC20BT
Long Battery Life (# of tests)	-	~	~	~		~
4 AAAklakine or NiMH Rechargeable Batteries Superior Pump Sampling Backlit LCD Screen Chart Alcohol Curve 10 sec. response time 30 sec. recovery time Prop Standards: IEC 68-2-32 Shock Standards: IEC 68-2-32 Shock Standards: IEC 68-2-29 Wibration Standards: IEC 68-2-29 Wibration Standards: IEC 68-2-29 Wibration Standards: IEC 68-2-29 Wibration Standards: IEC 68-2-5 Size: 2.6" x 5" x 1.25" Weight: 8 oz. (226 grams) Protective Silicone Grip Best in Class Operating Temperature 32" - 130"F (0" - 55"C) User Selectable Test Mode Temperature Lockout Automatic Self Diagnostics Auto Shut-Off Icon Driven User Interface Passive Testing Automatic Testing Wulti-Language Capabilities Preath Flow Graph Detection Range: 000 to .600 BAC Accuracy: ± .005 to 100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Software Compatible Data Input Fields Printing Capability Biuetooth Communication Indicator Light Wireless Reyboard Capability Bluetooth Communication with Other	Battery Status Indicator & Warnings	~	V	V	V	~
NIMH Rechargeable Batteries Superior Pump Sampling V V V V V V V V V V V V V V V V V V V	Long Battery Life (# of tests)	4700	6000	6000	6000	1900
Backlit LCD Screen Chart Alcohol Curve ≤ 10 sec. response time ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓		~	>	>	>	~
Chart Alcohol Curve	Superior Pump Sampling	V	V	~	~	~
\$ 10 sec. response time	Backlit LCD Screen	~	V	~	~	~
≤ 30 sec. recovery time ✓ <td>Chart Alcohol Curve</td> <td>~</td> <td>~</td> <td>~</td> <td>~</td> <td>~</td>	Chart Alcohol Curve	~	~	~	~	~
Drop Standards: IEC 68-2-32 Shock Standards: IEC 68-2-29 Wibration Standards: IEC 68-2-29 Vibration Standards: IEC 68-2-6 Size: 2.6' x 5' x 1.25' Weight: 8 oz. (226 grams) Protective Silicone Grip Best in Class Operating Temperature 32° - 130°F (0° - 55°C) User Selectable Test Mode Temperature Lockout Automatic Self Diagnostics Auto Shut-Off Icon Driven User Interface Passive Testing Multi-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Reminder Cal/Cal Check Reminder Cal/Cal Check Cokout Remaining Tests or Time before Lockout Data Input Fields Printing Capability Bluetooth Communication Indicator Light Wireless Reyboard Capability Bluetooth Communication with Other	≤ 10 sec. response time	~	V	~	~	~
Shock Standards: IEC 68-2-27 & IEC 68-2-29 Vibration Standards: IEC 68-2-6 Vibration Standards: IEC 68-2-20 Vibration S	≤ 30 sec. recovery time	~	~	~	~	~
IEC 68-2-27 & IEC 68-2-29 Vibration Standards: IEC 68-2-6 Size: 2.6" x 5" x 1.25" Weight: 8 oz. (226 grams) Protective Silicone Grip Best in Class Operating Temperature 32° - 130°F (0° - 55°C) User Selectable Test Mode Temperature Lockout Automatic Self Diagnostics Auto Shut-Off Icon Driven User Interface Passive Testing Automatic Testing Multi-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Communication with Other	Drop Standards: IEC 68-2-32	~	V	~	~	~
IEC 68-2-27 & IEC 68-2-29 Vibration Standards: IEC 68-2-6 Vibration Standards: Vibration Vi				J		
Size: 2.6" x 5" x 1.25"		-	-	-	-	·
Weight: 8 oz. (226 grams) Protective Silicone Grip Protective Silicone Grip Weight: 8 oz. (226 grams) V V V V Protective Silicone Grip Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V Weight: 8 oz. (226 grams) V V V V V Weight: 8 oz. (226 grams) V V V V V Weight: 8 oz. (226 grams) V V V V V V Weight: 8 oz. (226 grams) V V V V V V V Weight: 8 oz. (226 grams) V V V V V V V V V V Weight: 8 oz. (226 grams) V V V V V V V V V V V V V V V V V V V		V	V	~	~	~
Protective Silicone Grip Best in Class Operating Temperature 32*- 130°F (0*- 55°C) User Selectable Test Mode Temperature Lockout Automatic Self Diagnostics Auto Shut-Off Icon Driven User Interface Passive Testing Automatic Testing Automatic Testing Automatic Testing Wulti-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Bluetooth Communication Indicator Light Wireless Printing Capability Bluetooth Communication with Other		~	~	~	~	~
Best in Class Operating Temperature 32° - 130°F (0° - 55°C) User Selectable Test Mode Temperature Lockout Automatic Self Diagnostics Auto Shut-Off Icon Driven User Interface Passive Testing Automatic Testing Multi-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC ODT/NHTSA Approved On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Communication with Other		~	~	~	~	~
32° - 130°F (0° - 55°C) User Selectable Test Mode Temperature Lockout Automatic Self Diagnostics Auto Shut-Off Icon Driven User Interface Passive Testing Automatic Testing Multi-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Communication with Other	<u>'</u>	~	~	~	~	~
Temperature Lockout Automatic Self Diagnostics Auto Shut-Off Icon Driven User Interface Passive Testing Automatic Testing Automatic Testing Multi-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Reminder Cal/Cal Check Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Communication with Other	32° - 130°F (0° - 55°C)	~	~	~	~	•
Automatic Self Diagnostics Auto Shut-Off Icon Driven User Interface Passive Testing Automatic Testing Automatic Testing Multi-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC,	User Selectable Test Mode	~	~	~	~	~
Auto Shut-Off Icon Driven User Interface Passive Testing Automatic Testing Wulti-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Communication with Other	Temperature Lockout	V	~	~	~	~
Icon Driven User Interface	Automatic Self Diagnostics	~	~	~	~	~
Passive Testing Automatic Testing Multi-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC,	Auto Shut-Off	~	V	~	~	~
Automatic Testing Multi-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory Cal/Cal Check Reminder Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Connectivity Bluetooth Communication with Other	Icon Driven User Interface	~				
Multi-Language Capabilities Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Communication with Other	Passive Testing	~	~	✓	~	~
Breath Flow Graph Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC,	Automatic Testing		~	~	~	~
Detection Range: .000 to .600 BAC Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Multi-Language Capabilities		~	~	~	~
Accuracy: ± .005 to .100 BAC, ± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Printing Capability Bluetooth Connectivity Bluetooth Communication with Other	Breath Flow Graph		~	~	~	~
± 5% between .100 to .400 BAC DOT/NHTSA Approved On Board Test Memory 100 4000 4000 Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Detection Range: .000 to .600 BAC		V	~	~	~
On Board Test Memory Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other			~	~	~	~
Results Display: BAC or Pass, Warn, Fail Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	DOT/NHTSA Approved		~	~	~	~
Real Time Clock Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	On Board Test Memory			100	4000	4000
Password Protection Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Results Display: BAC or Pass, Warn, Fail			~	~	~
Cal/Cal Check Reminder Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Real Time Clock			~	~	~
Cal/Cal Check Lockout Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Password Protection			~	~	~
Remaining Tests or Time before Lockout Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Cal/Cal Check Reminder			~	~	~
Display Breath Flow Volume in Liters while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Cal/Cal Check Lockout			✓	~	~
while Blowing AlcoMark® Software Compatible Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Remaining Tests or Time before Lockout			~	~	~
Data Input Fields Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other				>	~	~
Printing Capability Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	AlcoMark® Software Compatible			~	~	~
Barometric Pressure Sensor (optional) Bluetooth Communication Indicator Light Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Data Input Fields				~	~
Bluetooth Communication Indicator Light Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Printing Capability				~	~
Wireless Printing Capability Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Barometric Pressure Sensor (optional)				~	~
Wireless Keyboard Capability Bluetooth Connectivity Bluetooth Communication with Other	Bluetooth Communication Indicator Light					~
Bluetooth Connectivity Bluetooth Communication with Other	Wireless Printing Capability					~
Bluetooth Communication with Other	Wireless Keyboard Capability					~
	Bluetooth Connectivity					~
	Bluetooth Communication with Other					~

Product Innovation

- Advanced Feature Set
- Customizable Software
- Password Protection & Lockout Features
- AlcoMark® Software Compatible
- Data Management Solutions

Precision Instruments

- Platinum Fuel Cell with lifetime warranty
- Superior Pump Sampling System
- Rapid & Repeatable Test Taking
- Fastest Response Times
- Widest Operating Temperature
- Barometric Pressure Sensor (optional)

Ease of Use

- Automatic Operation
- Menu Selectable Features
- Easy to Understand Prompts with Full Text Alerts
- Sturdy & Rugged Design
- Long Battery Life

Five Star Customer Care

- Live, Onsite Technical Support
- Fast Repairs, 5 days or less
- Comprehensive Service Packages
- Affordable Product, Solutions & Supplies
- All Product Manufactured & Serviced Responsibly in USA



12441 West 49th Avenue, Suite 4 Wheat Ridge, CO 80033 303.431.9500 | 800.722.4872 fax: 303.431.1423

www.lifeloc.com